

K A U F M A N

PRODUCT
INFORMATION

**KAUFMAN
PRODUCTS
INC.**

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

K Pro HP Grout Aggregate

Description

K Pro HP Grout Aggregate is a washed, oven-dried specially graded aggregate. It is recommended for use with both K Pro and SurePoxy epoxy compounds to produce excellent grouts. Depending on which epoxy compound you use, the mixing ratio will vary from approximately 2 to 4 parts by volume for each part epoxy by volume. One unique advantage to K Pro HP Grout Aggregate is that the unique blend of aggregates increases the flowability of epoxy resins when used at the correct mix ratio.

Packaging

Moisture resistant 40 lb. bag.

Precautions

Read Material Safety Data before using.

Chemical Analysis

Silicon Dioxide	99.4%
Iron Oxide	.2
Aluminum Oxide	.2
Titanium Dioxide	.1
Calcium Oxide	.01
Magnesium Oxide	Trace

Typical Screen Analysis

Mesh	% Retained
16	36.3
20	24.1
30	19.1
40	10.8
50	1.5
70	7.2
100	.5
140	1.3

F:\T\Eng. Literature w-out Heading\127 Aggregate.doc

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.