

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

SureGrout 32

Description

SureGrout 32 grout mix is a specially formulated mix of blended dry inorganic compounds, special cements, tough, high strength properly graded quartz aggregates, plus other proprietary ingredients. When combined with 50% by weight of nominal 3/8" pea gravel, and mixed with potable water, it produces a durable, low shrink concrete.

Uses

Ideal for areas where small quantities of concrete are needed, and use of ready-mix concrete is not available or too costly. Structural Columns & Decks, Foundation Underpinnings, Patching Holes & Cracked Sidewalks, Machinery Pads.

Technical Data

Compressive Strength-Grout Mix (ASTM C-109)

1 day	2,100 psi.
3 days	5,400 psi.
7 days	5,600 psi.
28 days	6,500 psi.

Compressive Strength-Concrete Mix (ASTM C-39) 50% by weight nominal 3/8" pea gravel

1 day	2,500 psi.
3 days	4,200 psi.
7 days	5,500 psi.
28 days	6,800 psi.

Set Time (ASTM C-266)

Initial:	4 hours
Final:	5.5 hours

Set Time (ASTM C-191)

Initial:	4.5 hours
Final:	6.5 hours

Directions

Grout: Blend one 50 lb. bag of SureGrout 32 with approximately ¾ gallons of potable water.

Concrete - Blend one 50 lb. bag of SureGrout 32 with approximately 25 pounds of nominal 3/8" pea gravel and ¾ gallons of potable water. Add additional water to bring to the desired consistency and place.

If adding additional water to achieve a specific consistency, then this will reduce the compressive strength of SureGrout 32. Likewise, less water added will increase the strength. Only use as much water as is necessary to place and finish the grout and or concrete mixes.

Packaging/Yield

50 lb. moisture resistant, 4 ply bag with polyethylene liner. Each bag yields .45 ft³. Addition of 50% by weight of nominal 3/8" pea gravel will increase yield to approximately .60 ft³ per bag.

Pumping

SureGrout can be pumped successfully using a ChemGrout CG-550P Grout pump and mixer or similar pump.

Shelf Life One year in original, unopened bags

Storage Conditions Store dry at 40-95°F

Color Concrete Gray

Working Time at 72°F 45 minutes

Technical Information

Test results were achieved under laboratory conditions. Statistical variations will occur based upon mixing methods, temperature & humidity, test methodology, site conditions, curing conditions, application methods, and equipment.

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc. shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salespeople, distributors and their salespeople have no authority to change the printed recommendations concerning the use of our products.