

K A U F M A N

PRODUCT INFORMATION

KAUFMAN PRODUCTS INC.

3811 CURTIS AVENUE

BALTIMORE, MARYLAND 21226-1131

410-354-8600 800-637-6372

www.kaufmanproducts.net

MATERIAL SAFETY DATA

Product Manufacturer:

Kaufman Products, Inc.
3811 Curtis Avenue.
Baltimore, Maryland 21226

Emergency Telephone No.

410-354-8600 (work hours)
800-424-9300 (other times)

Product Trade Name and Identification

Epoxy Resin Compound
SurePoxy DBA Code-213

Ingredients

	CAS#	TLV
A. Blend of liquid epoxy resins based on reaction products of epichlorohydrin and bisphenol A & Epichlorohydrin (ECH) content: 5 PPM max.- typically 1 PPM.	25068-38-6	50 ppm
B. Blend of complex aliphatic ether amines	68411-90-5	NA
Phenols	25154-52-3	5 ppm
Calcium Carbonate	1317-65-3	23.8mg/m ³
Hydrated Kaolin	1332-58-7	5 mg/m ³

TLV for pigments are for dust, however pigments Are totally encapsulated in liquid

Physical Data

Boiling Point: **A.** 360 °F, **B.** 500 °F
Solubility in Water: Nil
Vapor Density: Heavier than air
Appearance and odor: Light color liquid,
A. Ether odor, **B.** Amine odor
Evaporation Rate: Slower than ether
Percent Volatile by Volume: 3% max.
Weight per Gallon: **A.** 10.8, **B.** 12.1

Fire and Explosion Hazard Data

DOT Category: **A.** Epoxy Resin Compound, **B.** Corrosive Liquid
Extinguishing Media: Foam, Co2, dry chemicals
Unusual Fire and Explosion Hazards: Do not store near strong oxidants.
Special Fire Fighting Procedures: Avoid breathing

smoke. Wear NIOSH approved respirators and canisters. *Flash Point:* **A.** 480 °F, **B.** 200 °F

Health Hazard Data

Threshold Limit Value: 50 ppm
Effects and First Aid Procedures: Overexposure: Primary irritation of skin with prolonged or repeated contact, but may cause strong sensitization.
Inhalation - Remove patient from exposure, administer artificial respiration and oxygen if necessary. *Skin Contact -* Remove saturated clothing and wash affected areas with soap and water. *Eye Contact -* Promptly flush with clean water. If irritation continues, call a physician.
Ingestion - Do not induce vomiting. Give liquids and call a physician immediately.

Reactivity Data

Stability: Stable
Hazardous Decomposition Products: Strong oxidizing agents
Hazardous Polymerization: Will not occur

Spill or Leak Procedures

Steps to be Taken In Case Material Is Released Or Spilled: Prevent ignition. Stop leakage. Ventilate area. Absorb liquid with absorbent. Keep people away. Keep out of public sewers, streams and waterways.
Waste Disposal Method: Use government regulated chemical disposal company.

Special Protection Information

Respiratory Protection: Organic vapor type.
Ventilation: Local exhaust: as needed to comply with TLV.
Protective Gloves: Impervious (rubber, butyl, etc.)
Eye Protection: Goggles or face shield.
Other Protective Equipment: Apron

Special Precautions

Precautions to be taken in Handling and Storing: Store away from heat and sparks.
Other Precautions: THIS IS AN INDUSTRIAL PRODUCT. Use reasonable care. Keep containers closed when not in use.

Date Prepared

April 27, 2010

F:\T\Eng. MSDS with Heading\213.doc Apr. 27, 10