

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
[www.kaufman
products.net](http://www.kaufmanproducts.net)

AMERICAN OWNED & MANUFACTURED

MATERIAL SAFETY DATA

Product Manufacturer

Kaufman Products, Inc.
3811 Curtis Avenue
Baltimore, Maryland 21226

Emergency Telephone No.

410-354-8600 (work hours)
800-424-9300 (other times)

Product Trade Name and Identification

Liquid Epoxy Coating
K Pro UC Putty Code-226
Component A

Ingredients CAS# TLV

Reaction product of epichlorohydrin & bisphenol A.	25068-38-6	50 ppm
These raw materials are consumed in the manufacturing process. Residual levels of epichlorohydrin are controlled to 1 ppm. max in this product. Residual levels of Bisphenol A are typically 1-10 ppm.		
Titanium dioxide	13463-67-7	10 mg/m ³

Physical Data

Boiling Point: 500
Solubility in Water: None
Vapor Density: Heavier than air
Appearance and odor: Clear or pigmented liquid of low
viscosity characteristic odor.
Evaporation Rate: Slower than ether
Percent Volatile by Volume: 1.0 max.
Weight per Gallon: 11.5

Fire and Explosion Hazard Data

DOT Category: NA
Extinguishing Media: Foam, dry chemical water
Unusual Fire and Explosion Hazards:
Avoid contact with liquid and breathing of smoke.
Flash Point: 480° F

Health Hazard Data

Threshold Limit Value: 50 ppm
Effects and First Aid Procedures: Overexposure:
Irritation to skin and, especially, eyes. Could cause a rash,
burn, or an asthmatic type response in sensitized persons.

Possible permanent eye injury. Ingestion - Do not induce
vomiting. Give large amounts of water and at least, 1 ounce of
vinegar in equal amounts of water. Call a Physician.

Inhalation - Supply fresh air. Eye Contact - Flush with copious
amounts of water for 15 minutes. Call a Physician. Skin
Contact - Remove contaminated clothing. Wash with soap and
water for 15 minutes.

Reactivity Data

Stability: Stable
Hazardous Decomposition Products:
Strong oxidizing agents such as acids and bases. Carbon
monoxide, aldehydes and other organics.
Hazardous Polymerization: Will not occur.

Spill or Leak Procedures

*Steps to be Taken In Case Material Is
Released Or Spilled:* Stop leak. Clean with cloth or absorbent.
Waste Disposal Method: Government approved chemical
disposal or landfill.

Special Protection Information

Respiratory Protection: NIOSH approved organic respirator.
Ventilation: Local exhaust
recommended. *Protective Gloves:* Butyl or rubber
Eye Protection: Goggles or face shield must be worn. *Other
Protective Equipment:* Apron, boots

Special Precautions

Precautions to be taken in Handling And Storing:
Store in cool place away from sparks and flame.
Other Precautions: THIS IS AN INDUSTRIAL PRODUCT. Keep
out of the reach of children.

Date Prepared

May 10, 1999

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.