

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372

www.kaufmanproduct.net

MATERIAL SAFETY DATA

Product Manufacturer

Kaufman Products, Inc.
3811 Curtis Avenue
Baltimore, Maryland 21226

Emergency Telephone No.

410-354-8600 (work hours)
800-424-9300 (other times)

Product Trade Name and Identification

Liquid epoxy sealer
Component A
Super Floor System Codes-725-730
Base Coat Clear and Colors

Ingredients	CAS#	TLV
Epoxy resins	25036-25-3	NA
Propylene glycol methyl ether	107-98-2	
Aromatic hydrocarbons	1330-20-7	100 ppm
If pigmented:		
Iron oxides	1309-37-1	NA
Titanium dioxide	13463-67-7	NA

Physical Data

Boiling Point: 248°F
Solubility in Water: Nil
Vapor Density: Heavier than air
Appearance and odor: Clear liquid, characteristic odor. Pigmented: Paint consistency and colored, characteristic odor.
Evaporation Rate: Slower than ether
Percent Volatile by Volume: 50
Weight per Gallon: 8.6

Fire and Explosion Hazard Data

DOT Category: Flammable
Extinguishing Media: Carbon dioxide, dry chemical, alcohol foam type or water spray for large fires.
Unusual Fire and Explosion Hazards:
Contains solvents. Do not use water to extinguish. When container is empty, do not burn or incinerate as trace amounts of contents can ignite or vaporize.
Special Fire Fighting Procedures:
Close container may explode when heated.
Flash Point: 94°F TCC

Health Hazard Data

Threshold Limit Value: 100 ppm
Effects and First Aid Procedures:
Overexposure: Inhalation - Lightheadedness, dizziness, headaches or unconsciousness. Remove patient from exposure, administer artificial respiration and oxygen if necessary. Call a physician. Skin Contact - Will dry and defat skin leading to dermatitis. Remove saturated clothing and wash affected areas with soap and water. Eye Contact - Promptly flush with clean water. If irritation continues, call a physician. Ingestion - Do not induce vomiting. Give liquids and call a physician immediately.

Reactivity Data

Stability: Stable liquid
Hazardous Decomposition Products: Thermal decomposition or burning may produce carbon monoxide and carbon dioxide.
Hazardous Polymerization: Will not occur

Spill or Leak Procedures

Steps to be Taken In Case Material Is Released Or Spilled:
Prevent ignition. Stop leakage. Ventilate area. Absorb liquid with absorbent. Keep people away. Keep out of public sewers, streams and waterways.
Waste Disposal Method: Use government regulated chemical disposal company.

Special Protection Information

Respiratory Protection: If ventilation adequate, none required. If not use NIOSH approved organic vapor mask and canister, or air supplied hose mask.
Ventilation: Local exhaust; as needed to comply with TLV. Protective Gloves: Impervious-(rubber, butyl, etc.)
Eye Protection: Goggles or face shield.
Other Protective Equipment: Apron

Special Precautions

Precautions to be taken in Handling and Storing: Keep away from fire, heat, sparks. Keep container tightly closed when not in use.
Other Precautions: THIS IS AN INDUSTRIAL PRODUCT. Keep out of the reach of children.

Date Prepared:

November 29, 1990

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.

