

K A U F M A N

PRODUCT
INFORMATION

**KAUFMAN
PRODUCTS
INC.**

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

SureForm 20

Description

SureForm 20 is a balanced blend of special alkali reactive fatty derivatives, and natural organic chemicals in a light clear hydrocarbon carrier that acts chemically and physically to prevent bonding between forms and concrete. The chemical ingredients adhere to the form and react with the alkali in the concrete to provide perfect releases you can count on. SureForm 20 leaves no residue and virtually eliminates cement dusting. After forms have been stripped, no clean-up is necessary before painting and plastering or tiling can proceed.

SureForm 20 is non-toxic, non-hazardous, noncarcinogenic, VOC compliant, and is biodegradable. It is safe to use.

Uses

SureForm 20 is recommended as a concrete form treatment, wherever unstained, easy stripping concrete surfaces, free of bug holes are desired. Forms and equipment used in handling concrete, treated with SureForm 20, last longer because it helps to waterproof wood forms, retard rusting of metal forms, as well as prevent concrete accumulation. It is recommended, with proper precautions, to prevent staining whenever white architectural concrete is used.

It is recommended for forms made of steel, aluminum, wood, PVC, ABS, etc.

Special Features Reduced cost- provides much greater coverage rates than conventional forms oils. Costs can be reduced by 50% due to increased coverage. Conventional form oils depend on a heavy coverage to work. SureForm 20 works the opposite way - a little goes a long way.

Cleaner Releases- Because of the alkali reactive fatty derivatives, you get a cleaner release than plain form oils. Surface defects are reduced and less oil is transferred to the concrete.

Longer Lasting Forms- the wood derivatives and the natural oil carrier protect the forms from water and rusting so that the forms last longer.

Specifications

Corps of Engineers CE-204, CE 1401.01 NavDock Spec. No. 56359/64

VOC/ Flash Point

VOC- 65 grams/liter- Meets applicable specifications Flash Point - > 350°F

Packaging

55 gallon drum (208.15 liters) 5 gallon pail (18.93 liters)

Application

Apply to dry, clean forms. SureForm 20 may be applied quickly and easily with our special sprayer. Brush, or roller may also be used. To obtain maximum benefit and performance, apply thin films. Excessive application will cause bug holes, discoloration, build-up and increased difficulty in stripping.

Coverage Rates

Steel, aluminum, high-density plywood- 1500 sq. ft./gal. Medium density plywood, paper column forms 1000 sq. ft./gal.

Precautions

Some black rubber forms will degrade when used with SureForm 20. Do not dilute. SureForm 20 will not cause staining, however, precautions should be taken to remove built-up rust, mill scale or old form oils. Test first to be sure performance is as desired. Not recommended as a bond breaker for tilt up concrete construction.

F:\TWWord Lit\020.doc Jan-04

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.