

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

FORMKOTE Emulsion

Description

FormKote Emulsion is a chemically active, water based, ready-to-use, concrete form release agent. It is formulated to be applied to forms prior to concrete placement to facilitate their removal following concrete placement. It contains organic compounds that react with the alkali content of concrete to form a bond breaking release film.

Use

FormKote Emulsion can be used on various types of forms. It will increase the life of wood forms by penetrating into the pores and protecting it from the elements. Equipment used in the concrete field can be protected from concrete sticking to it by applying this product while it is still clean.

Features

- Protects forms from weather damage.
- Lower cost due to higher coverage rates.
- Can be used on forms previously treated with other form release agents.
- When used properly, will not stain concrete.
- Use on concrete mixing and placing equipment to prevent build-up.
- Non-flammable
- Biodegradable
- VOC compliant
- Non-toxic
- Non-hazardous
- Low odor
- Freeze/thaw stable

Technical Data

Color:	White
Viscosity:	<20 cps.
Freezing Pt.	32 °F
Flash Point:	None

Compliance

CE-204
CW-03101
CEGS-03300

VOC

5 grams/liter - complies with all standards

Packaging

208.15 Liters (55 gal. drum)
18.93 Liters (5 gal. pail)

Directions

FormKote Emulsion is ready-to-use and should not be diluted. Apply by conventional methods, such as sprayer, dipping or mopping. If spraying, be sure to use a fine atomizing tip. Apply to clean, dry forms using care to prevent contact with reinforcing steel. Avoid puddles and runs. Clean application equipment with water. Protect freshly treated forms from rain until dry. If allowed to sit for a long time or if subjected to freezing, stir before using.

Coverage

600-1500 sq. ft. per gallon
Use the lighter rates on non-porous surfaces such as steel, fiberglass or plastic.

Precautions

This product will freeze, however it is not hurt by the freezing action. If frozen, allow to thaw and agitate before using. Read Material Safety Data before using. Test before using on white concrete to be sure the results are satisfactory. Applications in excess of our recommendations might interfere with adhesions of subsequently applied coatings or other applied products. To prevent the water in this product from causing grain raising, the use of SureForm Sealer is strongly recommended.

F:\TW\Word Lit\021e.doc Nov-09

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.