

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

FormKote Concentrate

Description

FormKote Concentrate is a concentrated chemically active concrete form release agent. It is designed to be diluted with Kerosene, #2 diesel fuel or heating oil. The concentrate contains all the chemicals necessary when combined with the diluents to produce a clean release from the concrete. The chemically active components, release by reacting with the concrete at the form surface. These bubbles act like tiny ball bearings and amount of diluents; FormKote Concentrate provides both a chemical as well as a physical release.

Uses

Use on all concrete forms to insure a good, clean release. Apply to all equipment and tools used around concrete and masonry to prevent buildup. May be used on wood, fiberglass or metal forms with equal success. FormKote Concentrate helps to protect metal and wood forms from weather damage.

VOC

423 grams/Liter -as furnished. Will not comply with VOC requirements after it is diluted because the VOC will be 516 grams/Liter then.

Flashpoint

160°F

Directions Dilution - Pour the contents of one well-stirred 5 gallon pail into a clean 55 gallon drum. Add 50 gallons of Kerosene, #2 diesel fuel or heating oil. Stir well until uniformly mixed.

Application

FormKote Concentration is ready to use after diluting.

Method - Apply by spraying, roller or brush. Apply to clean, reasonably dry forms using care to prevent contact with reinforcing steel. Avoid puddles and runs. Clean application equipment with SAC or mineral spirits.

Coverage

Plywood 600-800 sq. ft. per gallon. Steel or plastic 1500 sq. ft. per gallon. Treat bracket, tie rods, shoring and scaffolding daily or as required to soften existing build-up and prevent future accumulations.

Packaging

55 gallon drum (208.15 Liters)
5 gallon pail (18.93 Liters)

Precautions

Flammable. Contains petroleum distillates. Keep away from sparks and open flames. Store away from heat. Avoid ingestion, skin and eye contact and inhalation of spray units. Before applying subsequent applied coating, adhesive or sealants to concrete, cast against FormKote Concentrate, and test for proper adhesive first. If improved adhesion is desired, acid-etch, and clean and remove all traces of FormKote Concentrate. Test before use on white concrete to be sure results are satisfactory.

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.