

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

PATCHWELL FS

Description

Patchwell FS was developed especially to provide a fast setting, adhesive modified compound for leveling concrete. This product contains special modifying agents that offer some self-leveling properties and increased adhesion to the substrate. When properly used, you will never have to worry about shrinking or expansion. FS contains correct gradations of hard quartz aggregates, which provides for smooth troweling, even to featheredges. Includes our migrating corrosion inhibiting agent for long-lasting repairs.

Uses

Use as an underlayment to smooth and level floors prior to tile, carpets, or hard tile installation.

Advantages

Self Leveling
Single component
Sets in 15 minutes- Simple, just add water
Strength exceeds 3000 psi
Non-Shrinking
Non-Rusting
Durable - will not crumble up under loads
Compatible with all adhesives
Migrating Corrosion Inhibiting Agents

Directions

Add 1 gal. water to one 50 lb. bag of Patchwell FS and mix thoroughly for up to one minute. Only mix enough that can be used in 10 minutes. Apply to the already cleaned and dampened surface with a trowel and fill hole or depression. Trowel smooth. Do not add water to mix once it has started to harden.

Packaging

50 lb. bag

Coverage

50 lb. will cover approximately 50 sq.ft. @ 1/8" thick.

Precaution

Patchwell FS is not recommended for surfaces that have been subject to oil, grease, over stripped wood floors, or as a wearing surface use appropriate floor covering. Do not use in exterior areas subject to excessive moisture. For heavy loads use Patchwell Kit or SurePoxy Mortar. Read Material Safety Data before using.

Physical Properties @ 70°F,

50% relative humidity

Compressive strength 3650 psi
ASTM C-109

Shrinkage 0
ASTM C-157

All values approximate - will vary with temperature and humidity.

F:\T\Word Lit\095.doc Jan-04

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.