

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

SureCure 25 Gray

Description

SureCure 25 Gray is a pigmented, ready-to-use, acrylic rubber copolymer for curing and sealing of concrete slabs. Specifically designed for interior, exterior concrete, and masonry floors, SureCure 25 Gray imparts a pleasing color with a degree of opacity, which obscures variations in the color of the concrete due to poor placement and/or finishing.

Uses

SureCure 25 Gray can be used on new or aged concrete surfaces to provide a durable, long lasting membrane that is resistant to abrasion, chemicals, paint, oil, and grease. Surfaces to be treated can be damp or dry; interior or exterior. Unlike transparent, conventional plain rubber curing compounds, SureCure 25 Gray is highly resistant to discoloration caused by the sun's ultraviolet rays. Surfaces retain their brightness for longer periods of time without yellowing, are easier to clean and maintain, and contribute to better lighting levels.

Compliances

ASTM C-309, Type 1, Grade B
ASTM C-1315, Type II (modified to gray)
AASHTO M-148, Type 1, Grade B
CRD C-300
TT C-800

Packaging

5-gallon pail (18.93 Liters)

Coverage Rates

Sq.Ft. Per Coat Per Gallon

Curing only 350-400

Dust proofing, Sealing & Renovating

1st Coat 300-400

2nd Coat 400-500

Coverage varies with texture and porosity of surface.

VOC

550 g/Liter

Directions

Surface Preparation

Newly placed Concrete: Surface must be sound and properly finished, Surface is application ready when it can no longer be marred by workmen. Stir well before using.

Aged Concrete

Surfaces must be free of gouges, dirt, oil, dust, grease, asphalt and other foreign matter. Use power tools and/or strippers to remove any incompatible sealers or coatings. Cleanse with caustic and detergents as required; rinse thoroughly and allow to dry until no more than damp. Surfaces to receive SureCure 25 Gray can be damp or dry, but never wet.

Application

Apply so as to form a continuous, uniform film by spray, long-nap roller or lambs wool applicator.

Precautions

Care should be taken not to apply SureCure 25 Gray to the interfacing of channels to be caulked with elastomeric sealants. This can be avoided by masking.

The application of SureCure 25 Gray over previously applied clear coating may result in reduced opacity and a more rapid wear of color.

Coverage on existing concrete will vary with textures and porosity. Clean equipment with SAC. THIS IS A HAZARDOUS MATERIAL, USE WITH CAUTION. Read Material Safety Data before using.

For more complete instructions, please refer to "Recommended Field Procedures for Curing & Sealing Compounds."

F:\TW\Word Lit\501.doc Oct-07

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.