

K A U F M A N

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufmanproducts.net

SureCure 25 Emulsion

Description

SureCure 25 Emulsion is an improved grade of our long-famous SureCure concrete treatment. It contains increased amounts of acrylic modified styrene copolymer solids for better sealing of the concrete surface from stains and provides a more dust proofed slab. It is classified as non-yellowing according to the new ASTM C-1315 specification. When tested under this specification and exposed to UV radiation, it is classified as resistant to yellowing and degradation.

Uses

This tough copolymer concrete treatment is designed for exterior and interior applications, above and below grade. Easily applied, SureCure 25 Emulsion provides a premium performance, long lasting shine to the floors. It is compatible with conventional carpet and resilient flooring adhesives. It is recommended for curing, hardening, dust proofing and sealing of both new and old concrete surfaces.

Compliances

ASTM C-309, Type I or ID, Class B
ASTM C-1315, Type I, Class B

Safety

VOC - <350 gm/Liter. Complies with specifications
Flash Point - None

Technical @75°F

NVM	25% min.
Dry Time	<1 hour
UV degradation	passes
Color	1 Gardner, max.
Adhesion, ASTM D 4541	passes
Alkali & Acid Resistance	passes

Packaging

55 gal. drums (208 liters)
5 gal. pails (18.9 liters)

Directions

Fresh Concrete - SureCure 25 Emulsion should be applied within 1-2 hours after completion of the finishing operation or as soon as possible after surface water has disappeared. Coat surface uniformly, leaving no pinholes or gaps, at a coverage rate of 300 - 350 sq. ft. per gallon. Apply with hand sprayers equipped with nozzles specifically designed for high solids curing compounds, such as. Chapin nozzle # 1-5937 or equal. Apply as soon as the surface is sufficiently hard, so that it will not be marred. Do not puddle. If using a power sprayer, we recommend Kaufman Products Power Sprayer, because it was specifically designed for quick and even applications of emulsions as well as oil thinned cures.

Apply second coat, after previous coat has dried at least overnight. Be sure both coats are dry and hard before opening slabs to traffic. Aged Concrete - Remove all foreign matter. Apply as described above, however coverage rate may vary from 300-500 sq. ft. per gallon depending on texture and porosity of surface.

Notes

This is an emulsified product and will freeze at temperatures below 32°F. If allowed to freeze, thaw thoroughly before use. Freezing will not harm the product. If stored for extended periods, agitate gently before use. This product is not recommended for application to surfaces previously treated with a form oil or release agent. Clean equipment with Easi Kleen EM. Do not thin. Do not apply to surfaces meant to receive a cementitious topping. When used on exterior concrete a light amber color may develop when applied at heavier application rates. Read Material Safety Data before using. This is an industrial product. It is not offered for residential or consumer use.

For more complete instructions, please refer to "*Recommended Field Procedures for Curing & Sealing Compounds.*"

F:\T\Word Lit\504.doc Feb-07

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.