

# K A U F M A N

PRODUCT  
INFORMATION

**KAUFMAN  
PRODUCTS  
INC.**

3811 CURTIS  
AVENUE

BALTIMORE,  
MARYLAND  
21226-1131

410-354-8600  
800-637-6372  
[www.kaufmanproducts.net](http://www.kaufmanproducts.net)

## EasiKleen EM

### Description

EasiKleen EM is a high strength blend of solvents and special emulsifiers designed to help remove hydrocarbon resin based concrete curing compounds from concrete surfaces. The balanced blend of ingredients penetrate and soften the film so that it can be removed easily with scrubbing from either floor scrubbers or stiff bristled brooms. EasiKleen EM replaces hazardous petroleum and chlorinated solvent based removal products. EM is easy to apply and rinse off with clean water.

It can also be used to break down and remove grease, oil and dirt stains – as well as rubber tire marks. Use it also for degreasing tools and equipment.

### Uses

EasiKleen EM removes both clear and pigmented resin, based curing compounds from concrete floors. EM will not change the color or roughness of the concrete surface, like water blasting and acid etching .

### VOC

763 grams/liter. (No regulatory requirements)

### Packaging

5 gal. pail  
55 gal. drum

### Coverage Rate

Approximately 100-200 sq. ft./gal.

### Surface Preparation

*For stripping hydrocarbon resin based concrete curing and sealing compounds :* Apply 1 gallon of full strength EasiKleen EM to 100-200 square feet of floor area. Allow to stand 5-30 minutes. If EasiKleen EM starts to dry, re-apply more. *Do not allow the surface to dry.*

Scrub the floor with stiff bristle mechanical cleaning equipment—either power or hand. Apply clean water and scrub again. Rinse the surface well using pressure water applied by nozzle on end of hose. Pick up debris with a wet pick-up vac and dispose of properly. If necessary, repeat the process until the desired results are achieved.

### Precautions

Multiple coats or heavy applications of curing compounds may necessitate multiple applications of EasiKleen EM. Avoid breathing of vapors. Exhaust fumes away from the user. Do not apply or use near food. Not recommended on resilient, asphalt tiles or painted surfaces. EM may soften rubber tires and cause them to become tacky. Use caution when operating wheeled equipment in these conditions. Read Material Safety Data sheet before using

F:\T\Word Lit\621September 06

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salesmen, distributors and their salesmen have no authority to change the printed recommendations concerning the use of our products.