

KAUFMAN

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY

1.1. Product Identifier

Product Form: Mixture

Product Name and Code:

K Pro UC Aggregate Code-227P

1.2. Intended Use of the Product

Use of the substance/mixture: Aggregate for extension of repair mortars or for use with epoxy to produce an epoxy mortar grout.

Use of the Substance/Mixture: For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company

Kaufman Products, Inc.

3811 Curtis Avenue

Baltimore, MD 21226-1131

410-354-8600

<http://www.kaufmanproducts.net/>

1.4. Emergency Telephone Number

Emergency Number : 800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC – Day or Night

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Carc. 1A H350

STOT SE 3 H335

STOT RE 1 H372

2.2. Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H350 - May cause cancer (Inhalation)

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salespeople, distributors, and their salespeople have no authority to change the printed recommendations concerning the use of our products.

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary Statements (GHS-US)

H372 - Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation)

: P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust, fume

P261 - Avoid breathing dust/fume

P264 - Wash exposed areas. thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear eye protection, protective gloves

P302+P352 - IF ON SKIN: Wash with plenty of soap and water

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313 - If exposed or concerned: Get medical advice/attention

P312 - Call a POISON CENTER or doctor if you feel unwell

P321 - Specific treatment (see Section 4)

P332+P313 - If skin irritation occurs: Get medical advice/attention

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

P337+P313 - If eye irritation persists: Get medical advice/attention

P362 - Take off contaminated clothing

P362+P364 - Take off contaminated clothing and wash it before reuse

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container to local, regional, national, and international regulations

2.3. Other Hazards

Other Hazards Not Contributing to the Classification: Crystalline silica exists in several forms, the most common of which is quartz. If crystalline silica (quartz) is heated to more than 870°C, it can change to a form of crystalline silica known as trydimite, and if crystalline silica (quartz) is heated to more than 1470°C, it can change to a form of crystalline silica known as cristobalite. The OSHA PEL for crystalline silica as trydimite and cristobalite is one-half of the OSHA PEL for crystalline silica (quartz).

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Quartz (Component)	(CAS No) 14808-60-7	70-90	Carc. 1A, H350 STOT SE 3, H335 STOT RE 1, H372

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Fly ash combustion residue (amorphous calcium-aluminum silicates)	(Cas No) 68131-74-8	10-30	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H332 STOT RE 1, H373
---	---------------------	-------	--

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: If medical advice is needed, have product container or label at hand.

First-aid Measures After Inhalation: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Rinse immediately with plenty of water. Gently wash with plenty of soap and water. Obtain medical attention if irritation persists.

First-aid Measures After Eye Contact: Immediately rinse with water for a prolonged period while holding the eyelids wide open. Seek medical attention if material is embedded in eye. If eye irritation persists: Get medical advice and attention.

First-aid Measures After Ingestion: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Repeated or prolonged inhalation may damage lungs. May cause an allergic skin reaction. Irritation to eyes, skin and respiratory tract. Causes damage to organs. May cause damage to organs through prolonged or repeat exposure.

Symptoms/Injuries After Inhalation: Dust of the product, if present, may cause respiratory irritation after an excessive inhalation exposure. May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: Abdominal pain.

Chronic Symptoms: Respiratory difficulties. May cause cancer. Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: None known.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: No particular fire or explosion hazard.

Reactivity: Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, oxygen difluoride, may cause fire. It dissolves in hydrofluoric acid and may produce a corrosive gas (silicon tetrafluoride).

5.3. Advice for Firefighters

Precautionary Measures Fire: Fight fire with normal precautions from a reasonable distance.

Firefighting Instructions: Not flammable. To prevent volatilization of resin components, cool containers with water spray.

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection During Firefighting: Use normal individual fire protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Avoid generation of dust during clean-up of spills. Recover the product by vacuuming, shovelling or sweeping. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up.

6.1.1. For Non-emergency Personnel

Protective Equipment: Wear suitable protective clothing, gloves and eye/face protection. Use recommended respiratory protection.

Emergency Procedures: Collect as any solid.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Avoid creating or spreading dust. Contain and collect as any solid.

6.2. Environmental Precautions

None known.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain and collect as any solid.

Methods for Cleaning Up: Avoid generation of dust during clean-up of spills. Recover the product by vacuuming, shovelling or sweeping. Vacuum must be fitted with HEPA filter to prevent release of particulates during clean-up.

6.4. Reference to Other Sections See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Do not breathe dust.

Precautions for Safe Handling: Avoid creating or spreading dust. See American Society of Testing and Materials (ASTM) Standard Practice E 1132-99a, "Standard Practice for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica."

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke in areas where product is used.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool place. Keep container tightly closed.

Incompatible Products: Oxidizing agent.

Incompatible Materials: In finely divided state: reacts with (strong) oxidizers. such as: hydrofluoric acid. Chlorine trifluoride. Oxygen difluoride. fluorine.

Storage Area: Store in dry, cool area.

Special Rules on Packaging: Keep container closed when not in use.

7.3. Specific End Use(s) Aggregate for extension of repair mortars or for use with epoxy to produce an epoxy mortar grout. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
Ceramic Microspheres (66402-68-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ (inhalable particulate) ; 3 mg/m ³ (respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) ; 5 mg/m ³ (respirable fraction)

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Avoid dust production.

Personal Protective Equipment

: Dust formation: dust mask. Gloves. Safety glasses.



Hand Protection

: Cloth gloves.

Eye Protection

: Safety glasses.

Skin and Body Protection

: Handle in accordance with good industrial hygiene and safety practice. Always wash your hands immediately after handling this product, and once again before leaving the workplace. Wear suitable protective clothing. Wash contaminated clothing before reuse.

Respiratory Protection

: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of dust are expected to exceed exposure limits.

Consumer Exposure Controls

: Do not breathe dust. Wear recommended personal protective equipment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Coarse Powder.
Odor	: Negligible.
Odor Threshold	: No data available
pH	: 10 - 12
Relative Evaporation Rate (butylacetate=1)	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: No data available

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Density	: No data available
Specific Gravity	: 3.15
Density	: Quartz
Solubility	: Water: 0.1 - 1 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, Kinematic	: No data available
Viscosity, Dynamic	: No data available
Explosive Properties	: No data available
Oxidizing Properties	: None known.
Explosive Limits	: No data available

9.2. Other Information No additional information available

SECTION 10: STABILITY AND REACTIVITY

- 10.1 Reactivity:** Contact with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, oxygen difluoride, may cause fire. It dissolves in hydrofluoric acid and may produce a corrosive gas (silicon tetrafluoride).
- 10.2 Chemical Stability:** Stable under normal temperature and pressure.
- 10.3 Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid:** Avoid formation of dust.
- 10.5 Incompatible Materials:** Avoid strong oxidizers.
- 10.6 Hazardous Decomposition Products:** Silicon oxides. Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity : Not classified

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg

Skin Corrosion/Irritation: Causes skin irritation. pH: 10 - 12

Serious Eye Damage/Irritation: Causes serious eye irritation. pH: 10 - 12

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Quartz (14808-60-7)	
IARC group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation. Causes damage to organs (lung/respiratory system)

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

K Pro UC Aggregate	
Additional information	<p>Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.</p> <p>Pre-existing lung diseases such as emphysema or asthma may be aggravated by exposure to dusts. Pulmonary function may be reduced by inhalation of respirable crystalline silica. Also lung scarring produced by such inhalation may lead to a progressive massive fibrosis of the lung which may aggravate other pulmonary conditions and diseases and which increases susceptibility to pulmonary tuberculosis. Progressive massive fibrosis may be accompanied by right heart enlargement, heart failure, and pulmonary failure. Smoking aggravates the effects of exposure.</p> <p>Accelerated Silicosis can occur with exposure to high concentrations of respirable crystalline silica over a relatively short period; the lung lesions can appear within five years of the initial exposure. The progression can be rapid. Accelerated silicosis is similar to chronic or ordinary silicosis, except that the lung lesions appear earlier and the progression is more rapid.</p> <p>Acute Silicosis can occur with exposures to very high concentrations of respirable crystalline silica over a very short time period, sometimes as short as a few months. The symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis can be fatal.</p>

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Dust of the product, if present, may cause respiratory irritation after an excessive inhalation exposure. May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: Abdominal pain.

Chronic Symptoms: Respiratory difficulties. May cause cancer. Repeated or prolonged exposure to respirable crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Acute silicosis can be fatal.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No additional information available

12.2. Persistence and Degradability

K Pro UC Aggregate	
Persistence and Degradability	Not readily biodegradable.

12.3. Bioaccumulative Potential

K Pro UC Aggregate	
Bioaccumulative Potential	Not expected to bioaccumulate.

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

No additional information available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Regional Legislation (waste): Disposal must be done according to official regulations.

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT Not regulated for transport

14.2 In Accordance with IMDG Not regulated for transport

14.3 In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

K Pro UC Aggregate	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2 US State Regulations

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Quartz (14808-60-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION

Revision date : 04/13/2020

Indication of Changes : Revision date.

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H232	May form combustible dust concentrations in air

KAUFMAN

PRODUCT
INFORMATION

KAUFMAN
PRODUCTS
INC.

3811 CURTIS
AVENUE

BALTIMORE,
MARYLAND
21226-1131

410-354-8600
800-637-6372
www.kaufman
products.net

K Pro UC Aggregate (227P)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

LIMITED WARRANTY

We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salespeople, distributors, and their salespeople have no authority to change the printed recommendations concerning the use of our products.

DISCLAIMER

The information provided in this Safety Data Sheet is believed to be accurate to the best of our knowledge, information and belief at the date of its publication. The information given is designed solely as a guide for the safe handling, use, processing, storage, transportation, disposal, and release by a person trained in chemical handling. This is not to be considered a warranty or quality specification. The information relates only to the specific material designated, and may not be valid for such material used in combination with any other materials or in any process, unless specified on either the latest version of our product data sheet or safety data sheet. Users and handlers of this product should make their own investigations to determine the suitability of the information provided herein for their own purposes.

SDS US (GHS HazCom) - US Only 10 pt 2

For professional use only. Not for sale to or use by the general public.

LIMITED WARRANTY We warrant our products to be of good quality and will replace material proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement, Kaufman Products, Inc makes no warranty or guarantee, expressed or implied, including warranties of fitness or merchantability, respecting its products, and Kaufman Products, Inc shall have no other liability with respect hereto. User shall determine the suitability of the product or the intended use and assume all risks and liability in connection thereto. Our salespeople, distributors, and their salespeople have no authority to change the printed recommendations concerning the use of our products.