

PRODUCT INFORMATION

KAUFMAN PRODUCTS INC. 3811 CURTIS AVENUE BALTIMORE, MARYLAND 21226-1131 410-354-8600 800-637-6372 www.kaufman products.net

K Pro HP Grout Aggregate

Description

K Pro HP Grout Aggregate is a low-dust, washed, oven-dried specially graded aggregate. It is recommended for use with both K Pro and SurePoxy epoxy compounds to produce epoxy grouts. Depending on which epoxy compound you use, the mixing ratio will vary from approximately 2 to 7 parts by volume for each part epoxy. K Pro HP Grout Aggregate is blended so that the unique blend of aggregates increases the flowability of epoxy resins when used at the correct mix ratio. Additionally, K Pro HP Grout Aggregate is further enhanced to be more user-friendly as a low-dust material.

Chemical Analysis		
Silicon Dioxide	99.4%	
Iron Oxide	.2	
Aluminum Oxide	.2	
Titanium Dioxide	.1	
Calcium Oxide	.01	
Magnesium Oxide		Trace

Typical Screen Analysis

Mesh	% Retained	
16	36.3	
20	24.1	
30	19.1	
40	10.8	
50	1.5	
70	7.2	
100	.5	
140	1.3	
	•	

Packaging

Moisture resistant 50 lb. bag.

Precautions

Read Safety Data Sheet before using.

Technical Information

The following results were achieved under laboratory conditions. Statistical variations will occur based upon mixing methods, temperature & humidity, test methodology, site conditions, curing conditions, application methods, and equipment.