



Product Description

Patchwell BSL is a single component, polymer-modified, vertical & overhead concrete repair mortar for use up to 3" deep in a single lift. Patchwell BSL is winter optimized to be resistant to the hazards of freeze-thaw cycling, deicing chemicals, and saltwater environments. Patchwell BSL is ideally suited for beam seat leveling, all types of structural repairs, and other types of general concrete restoration.

Section 1: Summary

Nested Method / Product Threshold

CONTENT INVENTORY

Inventory Reporting Format	Threshold Level	Residuals/Impurities Evaluation	For all contents above the threshold, the manufacturer has:
<input checked="" type="radio"/> Nested Materials Method	<input checked="" type="radio"/> 100 ppm	Completed in 6 of 6 Materials	Characterized <input checked="" type="radio"/> Yes <input type="radio"/> No
<input type="radio"/> Basic Method	<input type="radio"/> 1,000 ppm	Explanation(s) provided for Residuals/Impurities?	<i>Provided weight and role.</i> <input checked="" type="radio"/> Yes <input type="radio"/> No
Threshold Disclosed Per	<input type="radio"/> Per GHS SDS	<input checked="" type="radio"/> Yes <input type="radio"/> No	Screened <input checked="" type="radio"/> Yes <input type="radio"/> No
<input type="radio"/> Material	<input type="radio"/> Other		<i>Provided screening results using HPDC-approved methods.</i>
<input checked="" type="radio"/> Product			Identified <input checked="" type="radio"/> Yes <input type="radio"/> No
			<i>Provided name and CAS RN or other identifier.</i>

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

NESTED MATERIAL | MATERIAL OR SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

SAND [QUARTZ BM-1*] CAN | MAM | GEN **CEMENT [PORTLAND CEMENT LT-P1]** CAN | END | MAM **EXTENDER [CERAMIC MATERIALS AND WARES, CHEMICALS LT-UNK]** MUL **BINDER [HIGH-ALUMINA CEMENT LT-UNK]** **FILLER [SILICA FUME LT-P1]** CAN | MAM **ACCELERATOR [CALCIUM SULFATE HEMIHYDRATE LT-UNK]** MAM]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest-concern GreenScreen score(s) (BM-1, LT-1, LT-P1) ... LT-P1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

This HPD was produced using primary information from the manufacturer, including CAS numbers and SDS when needed. The manufacturer has made every effort to report the substances in this product to the listed threshold. This is a voluntary, self-reported effort. Any errors or omissions shall be considered a human error and therefore reported to the manufacturer. The manufacturer shall not be liable for omissions. The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.

*Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. For this reason, this score is intentionally omitted from the "Contents highest concern" line above. See HPDC's Special Conditions policy for more information.

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional listings.

VOC emissions: Inherently non-emitting source per LEED
VOC content: MAS Certified Green - VOC Content

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?

PREPARER: Self-Prepared

SCREENING DATE: 2023-12-05

☐ Yes
☒ No

VERIFIER:
VERIFICATION #:

PUBLISHED DATE: 2023-12-15
EXPIRY DATE: 2026-12-05

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.3, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-3-standard

SAND

%: 45.0000 - 65.0000

PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Geologically Derived Material
----------------------------	--	--

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: Percentages > 10% are used to disguise the formula covered as intellectual property.

QUARTZ

ID: 14808-60-7

HAZARD DATA SOURCE: Pharos Chemical and Materials Library		HAZARD SCREENING DATE: 2023-12-05 3:25:29	
---	--	---	--

%: 99.0000

GreenScreen: BM-1

RC: None

NANO: No

SUBSTANCE ROLE: Filler

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
CAN	US CDC - Occupational Carcinogens	Occupational Carcinogen**
CAN	CA EPA - Prop 65	Carcinogen - specific to chemical form or exposure route**
CAN	US NIH - Report on Carcinogens	Known to be Human Carcinogen (respirable size - occupational setting)**
CAN	MAK	Carcinogen Group 1 - Substances that cause cancer in man**
CAN	IARC	Group 1 - Agent is carcinogenic to humans - inhaled from occupational sources**
CAN	IARC	Group 1 - Agent is Carcinogenic to humans**
CAN	US NIH - Report on Carcinogens	Known to be a human Carcinogen**
CAN	GHS - Japan	H350 - May cause cancer [Carcinogenicity - Category 1A]**
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]**
CAN	GHS - New Zealand	Carcinogenicity category 1**
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]**
GEN	GHS - Japan	H341 - Suspected of causing genetic defects [Germ cell mutagenicity - Category 2]**
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]**
MAM	GHS - New Zealand	Specific target organ toxicity - repeated exposure category 1**
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
None found		No listings found on Additional Hazard Lists

SUBSTANCE NOTES: Per Pharos database: "Only a few elements can replace silicon in the quartz lattice (substitutional positions) or are small enough to occupy free spaces in the lattice (interstitial positions). In natural quartz crystals, the most common ones to replace Si are Al, Fe, Ge, and Ti, whereas Li, Na, Ca, Mg and Fe often occupy interstitial positions in the "c-channels". " [Mindat]

**Form-Specific Hazard: This substance's GreenScreen Benchmark or List Translator score and the applicable hazards are related to particulate inhalation, which is expected to occur only during manufacture, installation, maintenance, or demolition, due to activities such as sawing, sanding, grinding, or intensive cleaning. See HPDC's Special Conditions policy for more information. Manufacturer's Safety Data Sheet (SDS), if applicable, may offer occupational health and safety information.

CEMENT

%: 28.0000 - 40.0000

PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Geologically Derived Material
----------------------------	--	--

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: Portland Cement is made from materials mined from the earth, and may contain up to 0.75% insoluble residue, some of which may be free crystalline silica. Other trace Constituents may include free calcium oxide (also known as quick lime) and Chromium and Nickel may be at levels below 0.02%. (Continental Cement Company MSDS)

PORTLAND CEMENT

ID: 65997-15-1

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2023-12-05 3:25:29	
%: 95.0000 - 99.0000	GreenScreen: LT-P1	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	MAK	Carcinogen Group 3B - Evidence of carcinogenic effects but not sufficient for classification		
END	TEDX - Potential Endocrine Disruptors	Potential Endocrine Disruptor		
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		

SUBSTANCE NOTES: No residuals or impurities are expected to be present at or above 100 ppm.

EXTENDER

%: 4.0000 - 8.0000

PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Ceramic
RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.		

OTHER MATERIAL NOTES:

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2023-12-05 3:25:29	
%: 99.0000	GreenScreen: LT-UNK	RC: UNK	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
MUL	German FEA - Substances Hazardous to Waters		Class 3 - Severe Hazard to Waters	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
EXEMPT	European Union / European Commission (EU EC)		EU - REACH Exemptions	
			Exempted from REACH Annex V listing due to intrinsic safety	
SUBSTANCE NOTES: This material is identified on U.S EPA Safer Chemical Ingredients List.				

BINDER

?: 2.0000 - 6.0000

PRODUCT THRESHOLD: 100 ppm	RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes	MATERIAL TYPE: Geologically Derived Material
RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.		
OTHER MATERIAL NOTES: TSCA Definition 2008: High-Alumina cement is a mixture of chemical substances produced by burning or sintering at high temperature (greater than 1200.degree.C (2192.degree.F)) raw materials which are predominantly calcium carbonate, aluminum oxide, silica, and iron oxide.		

HIGH-ALUMINA CEMENT

ID: 65997-16-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2023-12-05 3:25:29	
%: 100.0000	GreenScreen: LT-UNK	RC: None	NANO: No	SUBSTANCE ROLE: Binder
HAZARD TYPE	LIST NAME AND SOURCE		WARNINGS	
None found			No warnings found on HPD Priority Hazard Lists	
ADDITIONAL LISTINGS	LIST NAME AND SOURCE		NOTIFICATION	
None found			No listings found on Additional Hazard Lists	
SUBSTANCE NOTES: No residuals or impurities are expected to be present at or above 100 ppm.				

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Other: Industrial by-product

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: Silica fume, a by-product of the ferrosilicon industry, is a highly pozzolanic material that is used to enhance mechanical and durability properties of concrete. It may be added directly to concrete as an individual ingredient or in a blend of portland cement and silica fume. (American Concrete Institute)

SILICA FUME

ID: 69012-64-2

HAZARD DATA SOURCE: Pharos Chemical and Materials Library			HAZARD SCREENING DATE: 2023-12-05 3:25:30	
%: 99.0000	GreenScreen: LT-P1	RC: PreC	NANO: No	SUBSTANCE ROLE: Filler
HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS		
CAN	GHS - Australia	H350i - May cause cancer by inhalation [Carcinogenicity - Category 1A or 1B]		
MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]		
MAM	GHS - Japan	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organs/systemic toxicity following repeated exposure - Category 1]		
MAM	GHS - Australia	H372 - Causes damage to organs through prolonged or repeated exposure [Specific target organ toxicity - repeated exposure - Category 1]		
ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION		
None found		No listings found on Additional Hazard Lists		
SUBSTANCE NOTES: Silica fume is a supplementary cementitious material (SCM) and is considered a pre-consumer waste product under the LEED program.				

ACCELERATOR

%: 2.0000 - 5.0000

PRODUCT THRESHOLD: 100 ppm

RESIDUALS AND IMPURITIES EVALUATION COMPLETED: Yes

MATERIAL TYPE: Geologically Derived Material

RESIDUALS AND IMPURITIES NOTES: Residuals and impurities are considered following the HPD Best Practice Guidance, 10.02.17, version 1 “The threshold applied to Residuals and Impurities (R/I) is the same as that applied to intentionally added substances, i.e., 100 ppm or 1000 ppm. Residuals and impurities below the declared Inventory Threshold do not need to be reported on the HPD.” This includes average data declared in the common product database or peer-reviewed scientific articles. For this product, no actual material has been tested. Therefore, residuals and impurities are for informational purposes only and are not a guarantee of presence in the actual building material. Pharos and PubChem (formerly TOXNET) are the main databases for researching potential residuals and impurities. Any R/I above the threshold shall be listed on the HPD; otherwise, if none are listed, then no residuals or impurities are common in that substance above the threshold.

OTHER MATERIAL NOTES: To protect confidentiality, percentages are shown in range.

HAZARD DATA SOURCE: Pharos Chemical and Materials Library

HAZARD SCREENING DATE: 2023-12-05 3:25:29

%: 100.0000

GreenScreen: LT-UNK

RC: None

NANO: No

SUBSTANCE ROLE: Accelerator

HAZARD TYPE	LIST NAME AND SOURCE	WARNINGS
-------------	----------------------	----------

MAM	GHS - Japan	H335 - May cause respiratory irritation [Specific target organ toxicity - Single exposure - Category 3]
-----	-------------	---

ADDITIONAL LISTINGS	LIST NAME AND SOURCE	NOTIFICATION
---------------------	----------------------	--------------

None found	No listings found on Additional Hazard Lists	
------------	--	--

SUBSTANCE NOTES: No impurities are expected to be present at or above 100 ppm.

Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

VOC EMISSIONS	Inherently non-emitting source per LEED	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2023-12-05	CERTIFIER OR LAB: None
APPLICABLE FACILITIES: 3811 Curtis Avenue, Baltimore, Maryland	EXPIRY DATE:	
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: Per the LEED v4.1, concrete is a non-emitting source. No VOC emission testing is necessary.		

VOC CONTENT	MAS Certified Green - VOC Content	
CERTIFYING PARTY: Self-declared	ISSUE DATE: 2023-12-09	CERTIFIER OR LAB:
APPLICABLE FACILITIES: 3811 Curtis Avenue, Baltimore, MD.	EXPIRY DATE:	kaufmanproducts
CERTIFICATE URL:		
CERTIFICATION AND COMPLIANCE NOTES: This is not MAS Green certification. The VOC content has been self-declared, utilizing the self-calculation method outlined by the United States Environmental Protection Agency (US EPA) and the South Coast Air Quality Management District (SCAQMD).		

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

USES:

Recommended for vertical and overhead concrete repairs.

Self curing.

Resurfacing damaged and honeycomb surfaces.

PACKAGING:

50 lb. bag of powder yielding 0.45 ft³

50 lb. pail yielding 0.45 ft³

MANUFACTURER INFORMATION

MANUFACTURER: Kaufman Products, Inc.
ADDRESS: 3811 Curtis Avenue
 Baltimore, Maryland 21226
COUNTRY: United States

WEBSITE: kaufmanproducts.net
CONTACT NAME: Alex Kaufman
TITLE: President
PHONE: 4103548600
EMAIL: akaufman@kaufmanproducts.net

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity	LAN Land toxicity	PHY Physical hazard (flammable or reactive)
CAN Cancer	MAM Mammalian/systemic/organ toxicity	REP Reproductive
DEV Developmental toxicity	MUL Multiple	RES Respiratory sensitization
END Endocrine activity	NEU Neurotoxicity	SKI Skin sensitization/irritation/corrosivity
EYE Eye irritation/corrosivity	NF Not found on Priority Hazard Lists	UNK Unknown
GEN Gene mutation	OZO Ozone depletion	
GLO Global warming	PBT Persistent, bioaccumulative, and toxic	

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)	LT-P1 List Translator Possible 1 (Possible Benchmark-1)
BM-3 Benchmark 3 (use but still opportunity for improvement)	LT-1 List Translator 1 (Likely Benchmark-1)
BM-2 Benchmark 2 (use but search for safer substitutes)	LT-UNK List Translator Benchmark Unknown
BM-1 Benchmark 1 (avoid - chemical of high concern)	NoGS No GreenScreen.
BM-U Benchmark Unspecified (due to insufficient data)	

GreenScreen Benchmark scores sometimes also carry subscripts, which provide more context for how the score was determined. These are DG (data gap), TP (transformation product), and CoHC (chemical of high concern). For more information, see 2.2.2.4 GreenScreen® for Safer Chemicals, www.greenscreenchemicals.org, and Best Practices for Hazard Screening on the HPDC website (hpd-collaborative.org).

Recycled Types

PreC Pre-consumer recycled content
PostC Post-consumer recycled content
UNK Inclusion of recycled content is unknown
None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material
Nested Method / Product Threshold Substances listed within each material per threshold indicated per product
Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology
Third Party Verified Verification by independent certifier approved by HPDC
Preparer Third party preparer, if not self-prepared by manufacturer
Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- *a method for the assessment of exposure or risk associated with product handling or use,*
- *a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.*

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this

